




Up to 5 year warranty

European quality - Danish design.
1100i™ comes with a 5 year warranty.



Possibility of 4 angled nozzles

1100i™ comes with a straight nozzle. However it can easily be exchanged with different angled nozzles with one or three holes straight or 30°.



XTRA+ fog fluid

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.



Tests & approvals

The model 1100i™ is tested and approved in accordance with IEC 62642-8 (a worldwide standard for fog cannon units). Test certificates can be obtained on protectglobal.com (documentation).

1100i™

Model 1100i™ is extremely powerful and fills the room very quickly. It's designed for protection of large spaces: office environments, large shops and storage facilities. Or even large private garages.



Features:

- Discharges 1300 m³ of fog at full speed in 60 seconds*
- Flexible adjustment between 500 and 1300 m³ to exactly fit the size of the room*
- 100 % silent in standby mode
- Pulse function for 4 min. (effective maintenance of the fog)
- Compatible with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- Prepared for 4 different angled nozzles and nozzle extension piece

Specifications:

Fog performance, example*: 60 sec. + 4 min. pulse: 1700 m ³
3 time settings from 500-1300 m ³ *
Optional pulse function (can shoot several times)
1,1 l. reusable fluid container included
Enough fluid for 4 discharges in one container
Electronic fluid measurement
Power consumption: 1350 W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 70 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 25 min.
Re-heating time after fog discharge: 0-8 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 1,5 hours
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White and black
Dimensions: L: 475, W: 332, H: 174 mm
Installation weight: 16 kg

**It's important to perform a test firing of the installation - and not only rely on the calculation of cubic metres.*

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS