




5 year warranty

European quality - Danish design.
2200i™ comes with a 5 year warranty.



Possibility of 4 angled nozzles

2200i™ comes with a straight nozzle. However it can easily be exchanged with different angled nozzles with one or three holes straight or 30°.



XTRA+ fog fluid

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.



NF&A2P 2 shields certified according to the NF324-H58 standard

Certifying organization: AFNOR (www.marque-nf.com) and CNPP (www.cnpp.com).
Applicable standards: EN 50131-8:2019 & RTC 50131-8.
Certificate number: 902400003A0.
Protection index: IP 20.
Mechanical shock protection index: IK08.
Security Grade 2.
Environmental Class II.
Operating temperature (min/max): 5/80 °C.

2200i™

Model 2200i™ is the most powerful fog cannon for anti-burglary protection. It has an enormous capacity and discharges with a massive roar. 2200i™ is designed for warehouses, large shops, shopping centers and buildings with mezzanines and large entrance ways.



Features:

- Discharges 2700 m³ of fog at full speed in 60 seconds*

The reduction in visibility to 1m during the tests carried out during the NF&A2P 2 shield certification (EN 50131-8: 2019 and RTC 50131-8) of the 2200i™ is 53 sec. for 150 m³ and 1236 sec. for maintaining opacity up to 3m.
- Flexible adjustment between 900 and 2875 m³ to exactly fit the size of the room*
- 100% silent in standby mode
- Pulse function for up to 10 min. (effective maintenance of the fog)
- Compatible with any alarm system
- Compatible with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- Prepared for 4 different angled nozzles and nozzle extension piece

Specifications:

Fog performance, examples*: 60 sec. + 10 min. pulse: 3700 m ³
3 time settings from 900-2875 m ³ *
Optional pulse function (can shoot several times)
3 l. reusable fluid container included
Enough fluid for 5 discharges in one container
Electronic fluid measurement
Power consumption: 1680 W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 80 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 30 min.
Re-heating time after fog discharge: 0-14 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 2,5 hours
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White and black
Dimensions: L: 633, W: 352, H: 172 mm
Installation weight: 24,8 kg

*It's important to perform a test firing of the installation - and not only rely on the calculation of cubic metres.

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS