




Up to 5 year warranty

European quality - Danish design.
600i™ comes with a 5 year warranty.



Possibility of 4 angled nozzles

600i™ comes with a straight nozzle. However it can easily be exchanged with different angled nozzles with one or three holes straight or 30°.



XTRA+ fog fluid

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.



Tests & approvals

The model 600i™ is tested and approved in accordance with IEC 62642-8 (a worldwide standard for fog cannon units). Test certificates can be obtained on protectglobal.com (documentation).

600i™

Model 600i™ is a classic in security fog protection and is our biggest seller. It covers most offices and shops and is also used in smaller stocks and private homes! 600i™ is close to being our professional, all-round fog cannon.



Features:

- Discharges 700 m³ of fog at full speed in 60 seconds*
- Turbo function to discharge 600 m³ in only 30 seconds*
- Flexible adjustment between 290 and 700 m³ to exactly fit the size of the room*
- 100 % silent in standby mode
- Pulse function for up to 9 min. (effective maintenance of the fog)
- Compatible™ with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Prepared for 4 different angled nozzles and nozzle extension piece

Specifications:

Fog performance, examples*: 30 sec.: 600 m ³ 60 sec.: 700 m ³ 60 sec. + 9 min. pulse: 1700 m ³
3 time settings from 290-700 m ³ *
Optional pulse function (can shoot several times)
1,1 l. reusable fluid container included
Enough fluid for 7 discharges in one container
Electronic fluid measurement
Power consumption: 1050 W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 60 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 15 min.
Re-heating time after fog discharge: 0-5 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 1,5 hours
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White and black
Dimensions: L: 475, W: 332, H: 154 mm
Installation weight: 12,6 kg

**It's important to perform a test firing of the installation - and not only rely on the calculation of cubic metres.*

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS